



EUCON 550

HIGH RANGE WATER REDUCING RETARDING ADMIXTURE

DESCRIPTION

EUCON 550 is a high range water reducing admixture formulated specifically to extend the working time of flowing concrete at high temperatures. EUCON 550 does not contain calcium chloride or any other ingredients that would promote the corrosion of steel.

PRIMARY APPLICATIONS

- Reinforced concrete
- High strength concrete
- Industrial slabs
- General Readymix Concrete
- Prestressed concrete
- Parking structures
- Watertight concrete

FEATURES/BENEFITS

- Produces "flowing" concrete with controlled delay of slump loss and workability.
- Greatly reduces water requirements.
- Reduces segregation and bleeding in the plastic concrete.
- Reduces cracking and permeability of hardened concrete.
- When used to produce "flowing" concrete, significantly reduces concrete placement time and cost.

PACKAGING

EUCON 550 is packaged in bulk 250 kg drums.

TECHNICAL INFORMATION

Physical State : Dark Brown Liquid
 Base Material : Sulphanated naphthalene formaldehyde condensates
 Specific gravity: 1.24 +/- 0.02 @25°C
 Air entrainment < or =1.5% over control mix
 pH: Minimum 6
 Chloride content: <0.2 %
 Compatible with all cement types like OPC, OPC+fly ash, PPC etc.,

SHELF LIFE

1 year in original, unopened container.

SPECIFICATIONS/COMPLIANCES

EUCON 550 meets or exceeds the following requirements:

- ASTM C 494, Type G
- AASHTO M 194
- IS9103/2007

DIRECTIONS FOR USE

Normal Dosage ranges -200 ml - 600 ml /50 kg of cement.

However the optimum dosage is determined by site trails.

Eucon 537 should be added to the initial batch water of the concrete mixture.

Do not dispense into dry cement.

Overdosing leads to retardation of setting times of concrete, mix may segregate and bleeding of concrete.

PRECAUTIONS/LIMITATIONS

- Care should be taken to maintain Eucon 550 above freezing. However freezing and subsequent thawing will not harm the material if thoroughly agitated.
- In all the cases consult safety datasheet before use.